



Mobile Racks B, C, R with chassis T for double sided use

JOWI Mobile Racks can be ordered with a telescopic chassis T for double sided use as an option. **Later on an adjustment is not possible. We recommend chassis T only after considering all aspects of use.**

Please consider the following effects of double-sided configuration of JOWI Mobile Racks:

- Double storing space, but no increase of maximum pay load
- Doubled space requirement for transport track if used as transport device during processing
- Reduced driving performance when manoeuvring
- If double sided Mobile Racks are used on one side only > maximum pay load is reduced compared to standard Mobile Racks.

For example: Maximum pay load R660-2/2: 500kg

Maximum pay load: for the entire Mobil Rack R660T-2/2: 500 kg,
double sided use: on the average maximal loading 250kg on each side;
single sided use: maximal loading 350kg due to construction!

As a result of all the facts above, our conclusion is, that in many cases in the long run two standard Mobile Racks would be more beneficial. Furthermore they are standing at your disposal on two different workstations when needed.

Equipment of backside of Mobile Racks with chassis T:

- Mobile Rack with frame cassis: I-uprights with support tubes can be positioned from front side to backside.
- Mobile Rack Type „R“ (R660 and R900): additional support tubes can be inserted at the backside into the vacant slots of the uprights.
- Mobile Rack Type B590 and C770 (to date B770) equipment level „X“ and „XX“: support tubes can be disassembled on the front side and inserted into the same slot at the backside > the result is an increased clearance between the support tubes (This is the only possibility for double sided use of this types of Mobile Racks).

Mobile Racks with chassis T with telescopic extension for temporary double sided use as capacity reserve:

- Mobile Rack with frame construction (equipment level 2/2)
The Mobile Rack can be used like a standard Mobile Rack. If needed cassis T can be extended and I-uprights with support tubes can be inserted to the backside. This provides adaptation within short time. It has to be considered that the minimum length of pieces to be stored on the front side is bigger then 1.520 mm. Otherwise additional I-uprights with support tubes will be needed.
- Mobile Racks type X and XX
To use this Mobile Racks temporary double sided, it requires more time for changing because disassembling and reassembling of support tubes at the backside is needed.



Illustration:

The picture shows an R660T-2/2 with extended telescopic cassis T and I- uprights with support tubes inserted to backside.

By loosening the handle nut on the cassis, it is possible to extend the cassis T for double sided use.

Finding the price:

Price of a standard Mobile Rack

+ Extra charge for cassis type T for double sided use

+ Additional support tubes / I-uprights with support tubes for the backside

= Price for double sided Mobile Rack